

## Welding mask



FBO-JL-A003  
Germany type  
ordinary len type (108x50x3mm)  
25pcs 13/12kgs  
52x45x52cm 5750pcs/20'



FBO-JL-A002  
Taiwan type  
ordinary len type  
(108x50x3mm)  
25pcs 14/13kgs  
47x45x49cm 6750pcs/20'



FBO-SCAL  
handhold outer handle  
(108x50x3mm)  
50pcs 16/14kgs  
79x24x62cm 12000pcs/20'



FBO-JL-A013  
handhold inner handle  
(108x50x3mm)  
40pcs 16/15kgs  
61x28x37cm 17720pcs/20'



FBO-HF403  
handhold inner handle  
(108x50x3mm)  
50pcs 19/18kgs  
49x44x40cm 16250pcs/20'



FBO-HF401  
handhold outer handle  
(108x50x3mm)  
50pcs 19/18kgs  
49x44x40cm 16250pcs/20'



FBO-JL-D006  
with Alu.bound  
PVC/PC visor  
headband clear splash proof  
40pcs 10/9kgs  
53x42x64cm 8200pcs/20'



FBO-JL-D036  
screen mesh shield  
40pcs 10/9kgs  
53x42x64cm 8200pcs/20'



FBO-JL-A007  
hardcap (108x50x3mm)  
50pcs 20/18kgs  
70x56x50cm 7250pcs/20'

EN175



FBO-JL-D002

visor and holder

100pcs 23/22kgs  
51.5x42x50.5cm 26000pcs/20'



FBO-CF2

visor holder (PVC/alu.)

100pcs 14/12kgs  
55x44x28cm 41500pcs/20'



FBO-E4003

headgear faceshield  
and helmet and ear muff  
12sets 13/12kgs  
60x48x56cm 2136sets/20'



FBO-D1001-1

material:  
PC/PVC with ALU edge  
size 8"x15.5"x1mm  
color:clear and dark  
125pcs/ctn 17/15kg  
61x33x23cm  
73750pcs/20'



FBO-D1001-2

material:  
PC/PVC without ALU edge  
size 8"x15.5"x1mm  
color:clear and dark  
125pcs/ctn 17/15kg  
61x33x23cm  
73750pcs/20'



FBO-D1001-3

material:mesh  
size 8"x15.5"x1mm  
color:black  
200pcs/ctn 14/12kg  
54x41x22cm  
115000pcs/20'

## Len



FBO-TH1 #5-#14

50mmx1.9mm black  
1000pcs 15/14kgs  
38x32x13cm  
1200000pcs/20'



FBO-TH2

50mmx1.5mm clear  
1500pcs 22/20kgs  
32x32x13cm  
1230000pcs/20'



FBO-TH4

108x50x2mm clear  
110x50x2mm clear  
600pcs 13/11kgs  
38x26x13cm  
831000pcs/20'  
600pcs 15/14kgs  
37x24x13cm  
771000pcs/20'



FBO-TH3 #9-#14

108x50x3mm black  
110x50x3mm black  
110x80x3mm black  
500pcs  
21/20kgs 38x32x13cm  
434000pcs/20'

## Auto Darken

Certificate: CE 

Surface finish treatment:black, painting, heat transfer printing

Packing:one piece with inner bag/color box

4pcs/ctn 5kgs/2kgs 54x54x32cm 1224pcs/20'

Special:one more piece ADF filter can be free of charge



FBO-1000B



FBO-800K



FBO-745



FBO-606



FBO-603



FBO-539



FBO-431



FBO-303



FBO-261



FBO-125



FBO-100



FBO-EH-985I

EN175

ADF series



power on/off: Automatic  
 power supply: solar cell and two 3v lithium batteries  
 operating temperature: -10°C ~ +55°C  
 storage temperature: -20°C ~ +70°C  
 material: ABS



**FBO-EF9030**  
 frame size: 108x50x6mm  
 view area: 90x30mm  
 range of UV/IR protection: up to shade DIN14 at all time  
 light shade: DIN3  
 dark shade: DIN 9 or DIN 11 **can't adjustment**  
 switching time: (light to dark): 1/20000s  
 switching time: (dark to light): 0.2-0.4s  
**sensivity: no**  
 weight: 0.06kgs  
 packing: 300pcs/ctn 19/18kgs 43x34.5x46cm



**FBO-EF9040**  
 frame size: 110x90x9mm  
 view area: 92x42mm  
 range of UV/IR protection: up to shade DIN16 at all time  
 light shade: DIN4  
 dark shade: DIN 9 or DIN 13, **external adjustment**  
 switching time: (light to dark): 1/25000s  
 switching time: (dark to light): 0.2-0.4s  
 sensitivy: low or high  
 weight: 0.118kgs  
 packing: 200pcs/ctn 24.8/23.6kgs 43x34.5x46cm



**FBO-EF9242** **Hight-quality LCD**  
 frame size: 110x90x9mm  
 view area: 92x42mm  
 range of UV/IR protection: up to shade DIN16 at all time  
 light shade: DIN4  
 dark shade: DIN 9 or DIN 13, **external adjustment**  
 switching time: (light to dark): 1/30000s  
 switching time: (dark to light): 0.2-0.4s  
 sensitivy: low or high  
 weight: 0.118kgs  
 packing: 200pcs/ctn 24.8/23.6kgs 43x34.5x46cm



**FBO-EF9242F** **Hight-quality LCD**  
 frame size: 110x90x9mm  
 view area: 92x42mm  
 range of UV/IR protection: up to shade DIN16 at all time  
 light shade: DIN4  
 dark shade: DIN 9 or DIN 13, external adjustment  
 switching time: (light to dark): 1/30000s  
 switching time: (dark to light): 0.1-1s steplessly adjustable  
 sensitivy: low or high steplessly adjustable  
 mode: weld/grind  
 weight: 0.12kgs  
 packing: 200pcs/ctn 25.2/24kgs 43x34.5x46cm



**FBO-EF9844** **Hight-quality LCD**  
 frame size: 110x90x9mm  
 view area: 98x44mm  
 range of UV/IR protection: up to shade DIN16 at all time  
 light shade: DIN4  
 dark shade: DIN 9 or DIN 13, **external adjustment**  
 switching time: (light to dark): 1/30000s  
 switching time: (dark to light): 0.1-1s steplessly adjustable  
 sensitivy: low or high steplessly adjustable  
 mode: weld/grind  
 weight: 0.122kgs  
 packing: 200pcs/ctn 25.2/24kgs 43x34.5x46cm



**FBO-EF10053** **Hight-quality LCD**  
 frame size: 110x90x9mm  
 view area: 100x53mm  
 range of UV/IR protection: up to shade DIN16 at all time  
 light shade: DIN3  
 dark shade: DIN 5-9 or DIN 9-13, external adjustment  
 switching time: (light to dark): 1/30000s  
 switching time: (dark to light): 0.1-1s steplessly adjustable  
 sensitivy: low or high steplessly adjustable  
 arc sensor: 4 low volum alarm ADF self-check  
 mode: weld/grind  
 weight: 0.126kgs  
 packing: 200pcs/ctn 26.4/25.2kgs 43x34.5x46cm